

	Type	L #	Hits	Search Text	DBs	Time Stamp
1	BRS	L6	137	(empirical data) same wafer same simulation same semiconductor	US- PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWEN T; IBM_TDB	2007/01/19 12:03
2	BRS	L7	11	(empirical data) same wafer same simulation same semiconductor same physical	US- PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWEN T; IBM_TDB	2007/01/19 12:05
3	BRS	L8	635	(empirical data) same wafer same simulation	US- PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWEN T; IBM_TDB	2007/01/19 12:06
4	BRS	L9	4	(empirical adj data) same wafer same simulation	US- PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWEN T; IBM_TDB	2007/01/19 12:06
5	BRS	L10	10	(empirical adj data) same semiconductor same simulation	US- PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWEN T; IBM_TDB	2007/01/19 12:06



simulation semiconductor physical "empirical"

Search

[Advanced Scholar Search](#)  
[Scholar Preferences](#)  
[Scholar Help](#)

**Scholar** [All articles](#) [Recent articles](#) Results 1 - 10 of about 709 for **simulation semiconductor physical "e**

**All Results**[J Eble](#)[A Dhodapkar](#)[G Fishman](#)[K Flamm](#)[C Lim](#)

**A GENERIC SYSTEM SIMULATOR WITH NOVEL ON-CHIP CACHE AND THROUGHPUT MODELS FOR GIGASCALE INTEGRATION** - group of 5 »

JC Eble III - 1998 - gigascale.org

... like to acknowledge the **Semiconductor** Research Corporation ... University System Performance**Simulator** (SUSPENS)....13 ... TIER CONSISTS OF ONE PHYSICAL LEVEL ...[Cited by 27](#) - [Related Articles](#) - [View as HTML](#) - [Web Search](#) - [Library Search](#)

**Worst case design parameter extraction for logic technologies** - group of 3 »

Z Krivokapic, WD Heavlin - US Patent 6,304,836, 2001 - Google Patents

... For example, the **semiconductor device simulator** may require ... Some of these parametersmay correspond to **physical** measurements of the device 200, such as ...[Cited by 5](#) - [Related Articles](#) - [Web Search](#)

**Analysis of mixed-signal manufacturability with statistical technology CAD (TCAD)** - group of 3 »

DA Hanson, RJG Goossens, M Redford, J McGinty, JK ... - **Semiconductor** Manufacturing, IEEE Transactions on, 1996 - [ieeexplore.ieee.org](#)... normally determined from destructive **physical** measurements or ... by 1M0B33, a National**Semiconductor** proprietary model ... the process and device **simulation**) takes 15 ...[Cited by 11](#) - [Related Articles](#) - [Web Search](#) - [BL Direct](#)

**Atomistic simulation of ion implantation and its application in Si technology** - group of 3 »

M Posselt, B Schmidt, T Feudel, N Strecker - Materials Science and Engineering B, 2000 - [elsevier.com](#)... the collection of a huge amount of **empirical data** on the ... The **physical** reason for the success of this model ... In the computer **simulation** of ion implantation into ...[Cited by 17](#) - [Related Articles](#) - [View as HTML](#) - [Web Search](#)

**Materials theory based modeling of wide band gap semiconductors: from basic properties to devices** - group of 2 »

KF Brennan, E Bellotti, M Farahmand, J Haralson, ... - Solid State Electronics, 2000 - Elsevier

... approximate since it neglects many important **physical** effects such as ... illustrated its application in the **simulation** of various **semiconductor** devices through ...[Cited by 15](#) - [Related Articles](#) - [Web Search](#) - [BL Direct](#)

**Manufacturability Metrics and RET Tradeoffs For Physical Design and Layout**

L Capodieci - Electronic Design Processes, 2003 - [eda.org](#)... **semiconductor** manufacturing costs for traditionally designed systems ... s set is released and **physical** designs are ... DR k a. Perform process **simulation** b. Extract ...[Cited by 2](#) - [Related Articles](#) - [View as HTML](#) - [Web Search](#)

**TEM 2 P 2 EST: A Thermal Enabled Multi-Model Power/Performance ESTimator - group of 4 »**

A Dhodapkar, CH Lim, G Cai, WR Daasch - Proc. PACS, 2000 - Springer

... the configuration file contains **physical** structure data ... These two **simulation** modes can be used ... domain data from TSMC (Taiwan **Semiconductor** Manufacturing Company ...

[Cited by 57](#) - [Related Articles](#) - [Web Search](#) - [BL Direct](#)

**Lump Partitioning of IC Bipolar Transistor Models for High-Frequency Applications - group of 4 »**

NN Chan, RW Dutton - [ieeexplore.ieee.org](#)

... parameter data taken from devices is compared to that generated from a two-lump model predicted by **physical** theory using 2-D finite element device **simulation**. ...

[Cited by 1](#) - [Related Articles](#) - [Web Search](#)

**Forecasting method for HEMT MMIC large-signal RF yield**

R Tsai, YC Chen, M Nishimoto, LW Yang, W Okamura, ... - [ieeexplore.ieee.org](#)

... We have found that Semi-**Physical** device modeling ... T. Ytterdal, and K. Lee, **Semiconductor**

Device Modeling for ... [4] H. R. Yeager, "Circuit **simulation** models for ...

[Cited by 1](#) - [Related Articles](#) - [Web Search](#)

**Intrafield Effects on Device and Circuit Manufacturability: A Statistical Simulation Approach - group of 4 »**

Z Krivokapic, WD Heavlin - IEEE TRANSACTIONS ON SEMICONDUCTOR MANUFACTURING, 1999 - [ieeexplore.ieee.org](#)

... the configuration of runs from the **physical** simulators ... with the least number of reactor **simulation** runs ... 444 IEEE TRANSACTIONS ON SEMICONDUCTOR MANUFACTURING, VOL ...

[Cited by 1](#) - [Related Articles](#) - [Web Search](#) - [BL Direct](#)

Google ►

Result Page:    1 2 3 4 5 6 7 8 9 10    **Next**

simulation semiconductor physical "

[Google Home](#) - [About Google](#) - [About Google Scholar](#)

©2007 Google